

2017 Columbia



STANDARD FEATURES	21'	23'	25'
2/3 Pro transom storage with single door	STD	STD	STD
Armor Tech™ premium floorboards with Dura Tuff™ non-skid vinyl covering	STD	STD	STD
Built in aluminum fuel tank with gauge	STD	STD	STD
Continuously welded box girder construction	STD	STD	STD
Columbia step deck three compartment (rope locker with Southco latch, dry storage with Southco latch, fish box)	STD	STD	STD
Electric bilge pump w/ auto switch	1200 GPH	2000 GPH	2000 GPH
Exclusive lifetime warranty	STD	STD	STD
Five switch panel with panel fuses, dual USB port, and 12-volt outlet	STD	STD	STD
Four deluxe comfort seats on adjustable aluminum storage boxes	STD	STD	STD
Four weld-on gunnel cleats located under coaming	STD	STD	STD
Full coaming gunnel	STD	STD	STD
Full length storage trays	STD	STD	STD
Full outside paint (single color / single stage)	STD	STD	STD
Rod grippers (four position)	STD	STD	STD
Running / mooring lights	STD	STD	STD
Six full length lifting / turning strakes	STD	STD	STD
Slotted chine and gunnel extrusions	STD	STD	STD
Stainless steel hinges on boxes and storage lids	STD	STD	STD
Two bolt-on transducer brackets	STD	STD	STD
Under floor protective coating	STD	STD	STD
Vinyl graphics	STD	STD	STD
Weld-on aluminum stern eyes	STD	STD	STD
Weld-on cleat on inner foredeck	STD	STD	STD
Weld-on double bow eye	STD	STD	STD
Weld-on zinc anode	STD	STD	STD
Zolatone interior	STD	STD	STD

ODEL SPECIFICATIONS				
Hull center length		21'5"	23'5"	25'5"
Beam		101"	101"	101"
Beam at the chine		82"	82"	82"
Inside freeboard		29"	29"	29"
Side height		33"	33"	33"
Transom height		31"	31"	31"
Deadrise	14	° RMV	14° RMV	14° RMV
Bottom thickness		.190	.190	.250
Side thickness		.125	.125	.160
Transom thickness		.190	.190	.190
Approx. weight	1	,925#	2,050#	2,250#
Persons / capacity	7/	1,050#	9/1,350#	9/1,350#
Weight capacity	1	,850#	2,120#	2,120#
Fuel capacity	5	0 Gal	50 Gal	50 Gal
Max. hp prop / jet	25	50/175	250/175	250/175