



# 2017 Free Drifter



STANDARD FEATURES	18'	20'
• Above floor fuel tank with gauge	STD	STD
• Aluminum transom door(s) with floor drains	STD	STD
• Armor Tech™ premium floorboards with Dura Tuff™ non-skid vinyl covering	STD	STD
• Continuously welded box girder construction	STD	STD
• Electric bilge pump	500 GPH	500 GPH
• Exclusive lifetime warranty	STD	STD
• Extended step deck with storage and fish box	STD	STD
• Five switch panel with fuses, dual USB port, and 12-volt outlet	STD	STD
• Four lifting / turning strakes	STD	STD
• Four weld-on gunnel cleats located under coaming	STD	STD
• Full coaming	STD	STD
• Full length storage trays	STD	STD
• Full outside paint (single color / single stage)	STD	STD
• Rod grippers	STD	STD
• Running lights	STD	STD
• Slotted chine and gunnel extrusions	STD	STD
• Straight transom	25"	27.5"
• Two bolt-on transducer brackets	STD	STD
• Two folding seats on aluminum boxes	STD	STD
• U.S. Coast Guard approved flotation	STD	N/A
• Under floor protective coating	STD	STD
• Vinyl graphics	STD	STD
• Weld-on cast aluminum stern eyes	STD	STD
• Weld-on cleat on inner foredeck	STD	STD
• Weld-on double bow eye	STD	STD
• Wide transom tray	STD	STD
• Zolatone interior	STD	STD

MODEL SPECIFICATIONS		
Hull center length	18'1"	20'1"
Beam	84"	84"
Beam at the chine	66"	66"
Inside freeboard	24"	24"
Side height	28"	28"
Transom height	25"	27.5"
Deadrise	6° w/ shoe	6° w/ shoe
Bottom thickness	.160	.160
Side thickness	.125	.125
Transom thickness	.160	.160
Approx. weight	1,240#	1,270#
Persons / capacity	5/750#	5/750#
Weight capacity	1,500#	1,500#
Fuel capacity	37 Gal	37 Gal
Max. hp prop / jet (remote)	115/80	115/80
Max. hp prop / jet (tiller)	75/80	75/80

Prices and specifications subject to change without notice.