



2017 Stryker Sport



STANDARD FEATURES	18'	20'
• Aluminum transom doors	N/A	STD
• Armor Tech premium floorboards with Dura Tuff™ non skid vinyl covering	STD	STD
• Bolt-on cleats (4)	STD	STD
• Built-in aluminum fuel tank with gauge	STD	STD
• Continuously welded box girder construction	STD	STD
• Deluxe dash panel with five switches, dual USB port, and 12-volt outlet	STD	STD
• Electric bilge pump	1200 GPH	1200 GPH
• Exclusive lifetime warranty	STD	STD
• Extra wide transom tray	N/A	STD
• Four gunnel cleats	STD	STD
• Full coaming aft of windshield	STD	STD
• Full length storage trays	STD	STD
• Full outside paint (single color / single stage)	STD	STD
• Mechanical steering	STD	STD
• Motor well / splash well	N/A	STD
• Navigation lights	STD	STD
• Rod grippers	STD	STD
• Saddle cut transom	20"	25"
• Slotted chine / gunnel extrusions	STD	STD
• Sound insulation package	STD	STD
• Starboard wiper	STD	STD
• Three bow custom top with side curtains and boot	STD	STD
• Two bolt-on transducer brackets	STD	STD
• Two comfort seats on aluminum boxes	STD	STD
• Two lifting / turning strakes	STD	STD
• U.S. Coast Guard approved flotation	STD	N/A
• Under console storage tray (port side)	STD	STD
• Under floor protective coating	STD	STD
• Vinyl graphics	STD	STD
• Vinyled control panel	STD	STD
• Welded aluminum glove box with locking door	STD	STD
• Welded aluminum step deck with storage	STD	STD
• Welded fish box in bow with lid	STD	STD
• Welded walk through windshield with lower walk through aluminum door	STD	STD
• Weld-on aluminum stern eyes and bow chock	STD	STD
• Weld-on double bow eye	STD	STD
• Zolatone interior	STD	STD

MODEL SPECIFICATIONS		
Hull center length	18'3"	20'3"
Beam	89"	89"
Beam at the chine	72"	72"
Inside freeboard	27.5"	27.5"
Side height	29"	29"
Transom height	20"	25"
Deadrise	14°	14°
Bottom thickness	.160	.160
Side thickness	.125	.125
Transom thickness	.125	.160
Approx. weight	1,350#	1,415#
Persons / capacity	5/750#	5/750#
Weight capacity	1,500#	1,500#
Fuel capacity	38 Gal	38 Gal
Max. hp prop / jet	115/80	135/80

Prices and specifications subject to change without notice.