

ALUMAWELD

2017 Super Vee



STANDARD FEATURES	20'
• Above floor fuel tank with gauge	STD
• Aluminum transom storage box with tray (3/4 offset port) with Southco latch	STD
• Armor Tech™ premium floorboards with Dura Tuff™ non-skid vinyl covering	STD
• Continuously welded box girder construction	STD
• Electric bilge pump	1200 GPH
• Exclusive lifetime warranty	STD
• Extended step deck with dry storage and fish box with Southco latches	STD
• Five switch panel with panel fuses, dual USB port, and 12-volt outlet	STD
• Four weld-on gunnel cleats located under coaming	STD
• Full coaming gunnel	STD
• Full length storage trays	STD
• Full outside paint (single color / single stage)	STD
• Rod grippers	STD
• Running/mooring lights	STD
• Six full length lifting/turning strakes	STD
• Slotted chine and gunnel extrusions	STD
• Stainless steel hinges on boxes and storage lids	STD
• Two bolt-on transducer brackets	STD
• Two deluxe comfort seats on aluminum storage boxes	STD
• Under floor protective coating	STD
• Vinyl graphics	STD
• Weld-on aluminum stern eyes	STD
• Weld-on double bow eye	STD
• Weld-on inner foredeck cleat	STD
• Zolatone interior	STD

MODEL SPECIFICATIONS	
Hull center length	20'3"
Beam	93.5"
Beam at the chine	72"
Inside freeboard	25"
Side height	30"
Transom height	20"
Deadrise	6°
Bottom thickness	.190
Side thickness	.125
Transom thickness	.190
Approx. weight	1,395#
Persons / capacity	6/900#
Weight capacity	1,700#
Fuel capacity	35 Gal
Max. hp prop / jet (remote)	115/105
Max. hp prop / jet (tiller)	115/80

Prices and specifications subject to change without notice.