



2019 Sport Skiff



STANDARD FEATURES	16'	18'	20'
• Aluminum fuel tank with gauge	Opt.	STD	STD
• Armor Tech™ premium floorboards with Dura Tuff™ non-skid vinyl covering	STD	STD	STD
• Continuously welded box girder construction	STD	STD	STD
• Electric bilge pump	500 GPH	500 GPH	500 GPH
• Exclusive lifetime warranty	STD	STD	STD
• Full length storage trays	STD	STD	STD
• Full outside paint (single color / single stage)	STD	STD	STD
• Motor well with storage	STD	STD	STD
• Navigation lights	STD	STD	STD
• Rod grippers	STD	STD	STD
• Saddle cut transom	20"	20"	20"
• Slotted chine and square gunnel	STD	STD	STD
• Two lifting / turning strakes	STD	STD	STD
• U.S. Coast Guard approved flotation	STD	STD	N/A
• Under floor protective coating	STD	STD	STD
• Vinyl graphics (Alumaweld name / stripe)	STD	STD	STD
• Welded aluminum step deck with storage box and fish box	STD	STD	STD
• Weld-on cast aluminum stern eyes	STD	STD	STD
• Weld-on double bow eye	STD	STD	STD
• Zolatone interior	STD	STD	STD

MODEL SPECIFICATIONS	16'	18'	20'
Hull center length	16'2"	18'2"	20'1"
Beam	77"	83"	83"
Beam at the chine	60"	66"	66"
Inside freeboard	23.5"	23.5"	23.5"
Side height	28"	29"	29"
Transom height	20"	20"	20"
Deadrise	10°	14°	14°
Bottom thickness	.160	.160	.160
Side thickness	.100	.100	.100
Transom thickness	.125	.125	.160
Approx. weight	740#	920#	950#
Persons / capacity	4/600#	5/750#	5/750#
Weight capacity	1,200#	1,500#	1,500#
Fuel capacity	Opt.	18 Gal	18 Gal
Max. hp prop / jet (remote)	60/40	115/80	115/80
Max. hp prop / jet (tiller)	40/40	50/40	115/80

Prices and specifications subject to change without notice.