



2019 Talon



STANDARD FEATURES	16'	18'
• Armor Tech premium floorboards with Dura Tuff™ non skid vinyl covering	STD	STD
• Bolt-on powder coated gunnel cleats (4) and aft foredeck cleat	STD	STD
• Built-in aluminum fuel tank with gauge	STD	STD
• Continuously welded box girder construction	STD	STD
• Deluxe dash panel with five rocker switch panel, dual USB port, and 12-volt outlet	STD	STD
• Electric bilge pump	500 GPH	500 GPH
• Exclusive lifetime warranty	STD	STD
• Full length storage trays	STD	STD
• Full outside paint (single color / single stage)	STD	STD
• Mechanical steering	STD	STD
• Motor well with storage	STD	STD
• Navigation lights	STD	STD
• Rod grippers	STD	STD
• Saddle cut transom	20"	20"
• Slotted chine / gunnel extrusions	STD	STD
• Sound insulation package	STD	STD
• Stainless steel hinges on boxes and lids	STD	STD
• Sun top with boot	Two bow	Three bow
• Two bolt-on transducer brackets	STD	STD
• Two folding seats on pedestals	STD	STD
• Two lifting / turning strakes	STD	STD
• U.S. Coast Guard approved flotation	STD	STD
• Under console storage tray (port side)	STD	STD
• Under floor protective coating	STD	STD
• Vinyl graphics	STD	STD
• Welded aluminum glove box with door	STD	STD
• Welded aluminum step deck with storage box and fish box	STD	STD
• Welded walk through windshield with lower walk through aluminum door	STD	STD
• Weld-on aluminum stern eyes	STD	STD
• Weld-on double bow eye and bow chock	STD	STD
• Zolatone interior	STD	STD

MODEL SPECIFICATIONS		
Hull center length	16'3"	18'3"
Beam	79.5"	84.5"
Beam at the chine	60"	66"
Inside freeboard	25"	25"
Side height	28"	29"
Transom height	20"	20"
Deadrise	10°	14°
Bottom thickness	.160	.160
Side thickness	.100	.100
Transom thickness	.125	.125
Approx. weight	885#	1,060#
Persons / capacity	4/600#	5/750#
Weight capacity	1,400#	1,500#
Fuel capacity	18 Gal	38 Gal
Max. hp prop / jet	70/50	115/80

Prices and specifications subject to change without notice.