



# 2021 Stryker X



STANDARD FEATURES	202 18°	220 18°
• Aluminum bow rails	STD	STD
• Aluminum transom doors with transom drain track	STD	STD
• Armor Tech premium floorboards with Dura Tuff™ non skid vinyl covering	STD	STD
• Bolt-on powder coated cleats	STD	STD
• Built-in aluminum fuel tank with gauge	STD	STD
• Continuously welded box girder construction	STD	STD
• Electric bilge pump	1200 GPH	1200 GPH
• Exclusive lifetime warranty	STD	STD
• Fish box in aft deck with lid	STD	STD
• Five switch panel with dual USB port and 12-volt outlet	STD	STD
• Foredeck storage locker with locking door	STD	STD
• Four spoke steering wheel	STD	STD
• Full outside paint (single color / single stage)	STD	STD
• Rod grippers	STD	STD
• Running / mooring lights	STD	STD
• Single heavy duty Alumadrive™ outboard bracket	STD	STD
• Starboard wiper	STD	STD
• Three bow custom top with side curtains, back drop and bag	STD	STD
• Three compartment between console storage	STD	STD
• Two bolt-on transducer brackets	STD	STD
• Two comfort seats on aluminum boxes	STD	STD
• Two lifting / turning strakes	STD	STD
• Under floor protective coating	STD	STD
• Vinyl graphics	STD	STD
• Welded aluminum glove box with door	STD	STD
• Welded storage box in bow with lid	STD	STD
• Welded walk through windshield w/door	STD	STD
• Weld-on aluminum stern eyes	STD	STD
• Weld-on double bow eye	STD	STD
• Weld-on zinc anode	STD	STD
• Zolatone or Tuff Dot interior	STD	STD

MODEL SPECIFICATIONS		
Hull center length	22'3"	24'3"
Beam	89"	89"
Beam at the chine	72"	72"
Inside freeboard	29.75"	29.75"
Side height	33.5"	33.5"
Transom height	25"	25"
Deadrise	18°	18°
Bottom thickness	.190	.190
Side thickness	.125	.125
Transom thickness	.250	.250
Approx. weight	1,685#	1,850#
Persons / capacity	6/900#	7/1,050#
Weight capacity	1,700#	1,900#
Fuel capacity	38 Gal	45 Gal
Max. hp prop / jet	150	200

Prices and specifications subject to change without notice.