



2021 Stryker Sport



STANDARD FEATURES	202 10°	202 14°	220 10°	220 14°
• Aluminum transom doors	STD	STD	STD	STD
• Armor Tech premium floorboards with Dura Tuff™ non skid vinyl covering	STD	STD	STD	STD
• Bolt-on powder coated cleats (4)	STD	STD	STD	STD
• Built-in aluminum fuel tank with gauge	STD	STD	STD	STD
• Continuously welded box girder construction	STD	STD	STD	STD
• Deluxe dash panel with five switches, dual USB port, and 12-volt outlet	STD	STD	STD	STD
• Depth finder box (port and stbd)	STD	STD	STD	STD
• Electric bilge pump	1200 GPH	1200 GPH	1200 GPH	1200 GPH
• Exclusive lifetime warranty	STD	STD	STD	STD
• Extra wide transom tray with hot box	STD	STD	STD	STD
• Foredeck with locking compartment	STD	STD	STD	STD
• Full coaming aft of windshield	STD	STD	STD	STD
• Full length storage trays	STD	STD	STD	STD
• Full outside paint (single color / single stage)	STD	STD	STD	STD
• Mechanical steering	STD	STD	STD	STD
• Motor well / splash well	N/A	N/A	STD	STD
• Navigation lights	STD	STD	STD	STD
• Rod grippers	STD	STD	STD	STD
• Saddle cut transom	STD	STD	STD	STD
• Slotted chine / gunnel extrusions	STD	STD	STD	STD
• Sound insulation package	STD	STD	STD	STD
• Starboard wiper	STD	STD	STD	STD
• Three bow custom top with side curtains, back drop and boot	STD	STD	STD	STD
• Two bolt-on transducer brackets	STD	STD	STD	STD
• Two comfort seats on aluminum boxes	STD	STD	STD	STD
• Two lifting / turning strakes	STD	STD	STD	STD
• Under console storage w/three locking compartments	STD	STD	STD	STD
• Under floor protective coating	STD	STD	STD	STD
• Vinyl graphics	STD	STD	STD	STD
• Vinyled control panel	STD	STD	STD	STD
• Welded aluminum glove box with locking door	STD	STD	STD	STD
• Welded aluminum step deck with storage	STD	STD	STD	STD
• Welded fish box in bow with lid	STD	STD	STD	STD
• Welded walk through windshield	STD	STD	STD	STD
• Weld-on aluminum stern eyes	STD	STD	STD	STD
• Weld-on double bow eye	STD	STD	STD	STD
• Weld-on zinc anode	STD	STD	STD	STD
• Zolatone or Tuff Dot interior	STD	STD	STD	STD

MODEL SPECIFICATIONS				
Hull center length	20'3"	20'3"	22'3"	22'3"
Beam	89"	89"	89"	89"
Beam at the chine	72"	72"	72"	72"
Inside freeboard	28.5"	30.25"	28.5"	30.25"
Side height	30"	33.5"	30"	33.5"
Transom height	25"	25"	25"	25"
Deadrise	10°	14°	10°	14°
Bottom thickness	.190	.190	.190	.190
Side thickness	.125	.125	.125	.125
Transom thickness	.190	.190	.190	.190
Approx. weight	1,460#	1,550#	1,625#	1,715#
Persons / capacity	5/750#	5/750#	6/900#	6/900#
Weight capacity	1,500#	1,500#	1,900#	1,900#
Fuel capacity	37 Gal	38 Gal	45 Gal	45 Gal
Max. hp prop / jet	150/105	150/105	200/140	200/140

Prices and specifications subject to change without notice.